



PRODUCT CODE

16121

SIZES AVAILABLE

16121-05 5 Gallon Container

➤ Weighs 50 lbs.

16121-55 55 Gallon Drum

➤ Weighs 500 lbs.

ALUM ONE is an aggressive blend of acids designed to brighten the dullest aluminum.

ALUM ONE can be used in a low pressure sprayer to degrease frames and motors prior to a vehicle wash. Dilute per the soil conditions and after a short dwell time rinse with high pressure.

CAUTION: Contains Hydrofluoric acid which is considered dangerous in any dilution. Wear protective clothes, gloves, and full face shield protection while handling this product.

HYDROFLUORIC ACID WILL DAMAGE GLASS.

Review the SDS sheet on this product for more specifics.

Technical info: Color: Clear pH
Concentrate: 0-1.0 Odor: Astringent

DILUTION RATE: Follow optimum dilution using cold water. May be diluted more with hot water.

ALUM ONE



ALUM ONE is a blend of both hydrofluoric & Sulfuric acid solutions. This product will brighten aluminum with a Satin Sheen appearance when used as directed.

ALUM ONE can be used when anodized or mirror polished surfaces have been damaged beyond restoring. This product can lessen that damaged look.

Optimum dilution of this product is 1 part chemical to 30 parts water when applied downstream with a pressure washer. Used in a pump sprayer, mix 4 ounces of chemical to each 1 gallon of water. In hard water areas more chemical may be required. Always test chemical in an 'out of the way' area. When cleaning with pressure washers, set the metering valve at desired dilution rate, and apply cleaning solution from the bottom up on a dry surface. Always detail clean from the bottom up and rinse from the top down.

5005 Belmar Blvd. Unit C-5 Farmingdale, NJ 07727

☎ 732-919-0800 ■ Fax 732-938-2621

gatewaycleaningequipment@gmail.com